

DYNAMIC FASTENER

Everything for the Metal Builder & Roofer®

9911 E. 53rd Street • P.O. Drawer 16837 • Raytown (K.C.), MO 64133-0937

NATIONAL 800-821-5448	KANSAS CITY 816-358-9898	FAX 800-844-1199	CHICAGO 708-615-1450	HOUSTON 713-647-8665	LAS VEGAS 702-566-1555	MEMPHIS 901-369-8000	ST. LOUIS 314-739-8771	ST. PAUL 651-644-1212	
	y Name								
	umah ar								
	umber								
Job Mam	e			_					
1) Who is	the panel mar	nufacturer?							
2) What c	does the panel	mfg. call this	panel profile?_						
3) What is	s the thickness	s (gauge) of th	is roof panel?						
4) What is	s the material t	this panel is m	nade of (steel,	copper, etc)?_					
5) Rafter length (eave-to-ridge dimension measured in pla					olan view) is			feet	
6) Roof s	lope is	:12							
7) Panels	seam spacicin	g is	inches.						
8) Panels	seam height is		inches.						
9) This quote is based on design roof snow (not ground snow) load of							pounds per square foot.		
(10) This ir	nformation was	s furnished by		of			_company.		
(11) This li	neal footage to	be protected	I by snow reter	ntion					
(12) Will th	ere be any ea	ve lengths pa	rtially but not c	ompletely prot	ected by DYN	A-GUARD?			

**Please include a rough sketch of the building to be protected including any adjacent buildings.

DYNA-GUARD should only be installed after proper design work was done by an engineer, architect, installer or building owner and it is the sole responsibility of the architect, designer, installer &/or building owner to assess the suitability of using **DYNA-GUARD** based on the above design considerations. Before installing **DYNA-GUARD** make certain that the roof & building can withstand the load and forces that will be exerted on this snow retention system. This load will be completely transferred to the building structure. Finally, no matter how much is designed into a system, Mother Nature will throw more at us than we have considered, such as drifting, ice, unusual amounts of snowfall, etc. Owners must be aware of these conditions and when these extremes are reached, snow and ice should be physically removed from the roof. Any snow retention system will not prevent possible wind-blown overhangs or cornices. The owner must be aware of these situations and remove them as they occur.